



Infrastructure product

Anybus Wireless Access Point IP67 with Mesh

The Anybus Wireless LAN access points provide you with wireless connectivity at high data rates. Developed for indoor and outdoor industrial settings and with wireless mesh, the Anybus Wireless LAN access points ensure a highly reliable network setup.



FEATURES & BENEFITS

HIGH THROUGHPUT WIRELESS PERFORMANCE

- Concurrent dual-band 2.4 GHz and 5 GHz WLAN, up to 867 Mbit/s + 300 Mbit/s bandwidth
- IEEE 802.11ac Wave 2 compliant, backward compatible with 802.11a/b/g/n

MESH SUPPORT

- Based on Qualcomm® Wi-Fi SON Technology
- Self-healing auto-rerouting through multi-hop (up to 8 hops)

RUGGED DESIGN FOR INDUSTRIAL APPLICATIONS

- Rugged design with IP30 or IP67 classed housing
- Waterproof cable glands for IP67 housing
- Effective heat dissipation design for operations in -40 to 70°C environments
- Support for Power over Ethernet, IEEE 802.3af

ENHANCED SECURITY AND REDUNDANCY

- Firewall for inbound/outbound traffic
- 1:1 NAT, port forwarding for local traffic protection
- Works seamlessly with the Anybus Wireless Bridge and Bolt

CERTIFICATIONS & APPROVALS

| | |
|---------------|---------|
| Europe | CE |
| North America | FCC, UL |

| | |
|--------------------------|--|
| Ethernet | LAN: 1 x 10/100/1000MBase-T RJ45, auto negotiation, auto-MDI/MDIX WAN: 1 x 10/100/1000MBase-T RJ45, auto negotiation, auto-MDI/MDIX |
| Antenna connector | 2 x N-type female |

| | |
|-------------------------------|---|
| Operating Temperature | -40 to 70 oC, 5 to 95 % RH non-condensing |
| WLAN standards | IEEE 802.11ac Wave 2 compliant, backward compatible with 802.11a/b/g/n/IEEE 802.11r (Fast roaming) 2.4 GHz / 5 GHz: 2T2R MU-MIMO DBDC (Dual-band dual-concurrent) |
| Data rates | 802.11ac: MCS 0-9, max. 867 Mbit/s 802.11b: 11Mbit/s, 802.11a/g: 54 Mbit/s, 802.11n: MCS 0-15, max. 300 Mbit/s |
| Mesh | Qualcomm® Wi-Fi SON Technology |
| USB | Reserved for future use |
| Power supply | IEEE 802.3af (48 VDC PoE, Max 11.5W) |
| Weight | 2 400 g |
| Housing material | Metal |
| IP class | IP67 |
| Dimensions | 269 x 239 x 68 mm without mounting bracket |
| Mounting | Pole/wall/ mount |
| Configuration | CGI WebGUI, Command Line Interface (CLI), SNMP, Telnet |
| Security | TLS v1.2, HTTPs/SSH, First login password management WLAN AP Security: WPA/WPA2-PSK, WPA/WPA2 Enterprise DMZ, IP/Port Filter NAT: 1-1 NAT, NAT(SNAT/DNAT), Port forwarding VPN: IPSec, OpenVPN, L2TP, GRE |
| Traffic management | Flow control, Traffic shaping |
| Network management | IPv4, SNMP v1/v2c/v3, DHCP server/client, SysLog, DDNS, DHCP relay, TFTP, SMTP, ARP response over 802.2 LLC SNAP, Proxy ARP, DNS client/proxy |
| Standards | CE Radio: RED Compliance CE Safety: IEC/EN60950-1, EN 55032, EN55035, EN51000-3-2, EN61000-3-3, EN301489-1/17, EN300328, EN301893, EN300400, N62311MPE FCC part 15B Class A |
| Product parts included | 1 x access point with pole mount AWB5142: 2 x antennas included |

| File | Version | Size | Read online |
|------|---------|------|-------------|
|------|---------|------|-------------|

Ordering Information

| | |
|----------------------------|--|
| Order Code | AWB5142 |
| Included components | Accesspoint |
| Accessories | AWB4005: PoE Injector 100-240V AWB4006: PoE Injector 12-57V |

near guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.

