Hitachi Commercial & VRF systems to KNX Interface with binary inputs

Item number: INKNXHIT001R000

The Hitachi-KNX interface allows full bidirectional communication between Hitachi Commercial & VRF systems and KNX installations. It has four potential-free binary inputs to integrate external devices (such as window contacts or presence detectors), with the corresponding internal functions available to help improve energy efficiency.

Hitachi to KNX - 1 indoor unit

Features and benefits

ETS configuration

The interface is configured using the ETS standard configuration tool software.

Multiple energy efficiency functions available

Timeout, open window, or occupancy energy-saving functions are available to reduce energy costs.

Total unit control and monitoring from KNX

Through internal variables, running hours counter (for maintenance purposes), and error indication.

AC unit control by both remote controller and KNX

The AC unit can be simultaneously controlled by the manufacturer's remote controller and KNX.

Compatible with all KNX thermostats in the market

All the required DPT objects to be compatible with all KNX thermostats in the market are available.

Smooth KNX thermostat integration

KNX thermostats are allowed to control the AC unit via the thermostat's temperature sensor.

Up to five scenes saved/executed from KNX

Up to five scenes can be saved and executed from KNX.

Compact dimensions, allowing inside installation

The interface can be quickly installed inside the AC unit thanks to its reduced dimensions.

14 rue Edouard Petit
42000 St-Etienne

Tel : +33 477 92 03 56
Email : contact@rg2i.com
www.rg2i.com

Hitachi Commercial & VRF systems to KNX Interface with binary inputs

General

Net Width (mm)	106
Net Height (mm)	58
Net Depth (mm)	90
Net Weight (g)	79
Packed Width (mm)	122
Packed Height (mm)	67
Packed Depth (mm)	93
Packed Weight (g)	136
Operating Temperature °C Min	-25
Operating Temperature °C Max	60
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Consumption (W)	0.232
Input Voltage (V)	29 VDC
Power Connector	2-pole
Configuration	ETS
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	Hitachi Commercial & VRF systems
Content of Delivery	Intesis gateway and installation manual.

Hitachi Commercial & VRF systems to KNX Interface with binary inputs

General

Not Included (in delivery)	Communication cables.
Mounting	Wall mount
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status

Product ID	INKNXHIT001R000
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	KNX, HVAC port, Binary inputs (dry contact).
LED Indicators	KNX
Contains Battery	No

Certifications and Standards

CE	Yes
CB	Yes
UKPSTI	Yes
UL	Yes
KNX	Yes
WEEE Category	IT and telecommunications equipment

Hitachi Commercial & VRF systems to KNX Interface with binary inputs

Use Case



Integration example.